

Uface Series Face Recognition time clocks



Uface 7 Access Control Series

- 99.99% recognition accuracy
- Recognition speed less than 1s
- Built-in card reader
- Live body detection
- Anti-backlight, WDR
- 1:1 and 1:N recognition mode
- Cable network, Wi-Fi
- 50-thousand (Max. 100-thousand) level face database

CPU	Dual-core ARM Cortex-A7@900MHz, 512M RAM +8GB ROM
Camera	2M pixel, Anti-backlight, WDR, Dual-camera
Display Screen	7-inch IPS all-sight LCD touch screen
External Interface	RS232, Digital output, Wiegand output, RJ45, USB
Operating System	Linux
Operating Voltage	DC 12V/2A
Dustproof & Waterproof	IP42
Temperature & Humidity	-10-50 °C , 10-90% RH
Dimension	247.40mm*127.00mm*24.00mm



Uface 8 Access Control Series

- 99.99% recognition accuracy
- Recognition speed less than 1s
- Built-in card reader
- Anti-backlight
- WDR, Wi-Fi
- Live body detection
- 1:1 and 1:N recognition mode
- Standard with 100,000 thousand face database

CPU	Dual-core ARM Cortex-A7, 512M RAM+8GB ROM
Camera	2M pixel, Anti-backlight, WDR, Dual-camera
Display Screen	8-inch IPS all-sight LCD touch screen
External Interface	RS-232, RS-485, USB, Wiegand output, Digital output
Operating System	Linux
Operating Voltage	DC 12V/2A
Dustproof & Waterproof	IP65
Temperature & Humidity	-10-50 °C , 10-90% RH
Dimension	272.50±0.20mm*133.00±0.20mm*87.63±0.60mm

What time did you start work today?